


Waterproof K-9 Camera **High Power version 2**



Part #: TSE-K9-KIT-WP-3.5-V2

The NEW Waterproof High Power K9 Camera Kit from Tactical Support Equipment Inc. is waterproof, salt water resistant with internal battery compartment. The system now incorporates a Color Day/Night Camera that visually outperforms any other K9 Camera in low light situations. The infrared illuminator is now controlled by the camera, so it is able turn the illuminator on and off as needed and save battery life.



The high power transmitter outputs at 3.5 Watts. The practical system transmission range is beyond 300 yards from a building and then through three reinforced concrete walls with steel hatch doors, giving it the furthest point-to-point transmission range of any K9 camera system on the market.

The Waterproof K9 Camera System is interoperable with all existing video equipment from TSE Inc and it still fits into most existing dog harnesses.





Features & Improvements

- **High Transmit Power of 3.5 Watts**
- **Video Output Connector on Camera** to adapt to Mesh Network Radios
- **Waterproof and Saltwater Resistant**
- **NEW Color Day/Night Low Light Camera**
- NEW Larger 3.5" LCD on Receiver/Monitor
- **Drop-in Replacement for Legacy K9 Camera Systems**

Available on GSA Schedule GS-35F-0039T

Tactical Support Equipment Inc. 4039 Barefoot Road Fayetteville, NC 28306

www.tserecon.com

For More Information Contact sales@tserecon.com





Phone: 800.889.4030 Phone: 910.425.3360

Fax: 910.425.3361

Specifications (TSE-K9-KIT-WP-3.5-V2)			
TRANSMITTER/CAMERA			
RF Power Output:	3.5 Watts		
Frequency Range:	886Mhz-923Mhz (Available in 1 of 6 Factory Preset Channels)		
Power Source:	12VDC (AA Batteries)		
Operating Time:	8 Lithium AA Batteries: 3.5 hrs. Typical 8 Alkaline AA Batteries: 1 hr. Typical		
Operating Temp:	-20 to 60° C / -4 to 140° F		
Environmental:	IP67 Water and dust proof		
Antenna:	Integrated Whip		
Video Signal:	NTSC		
Camera:	Day/Night, More than 750TVL of resolution		
Minimum illumination:	0.005 Lux F1.8 (AGC 54dB, IR LED OFF)		
	0 Lux (NIGHT mode, IR LED ON)		
Lens:	3.7mm lens F1.8		
IR illuminator:	Built-in @ 850nm, controlled by camera		
Video Output Port:	Waterproof Lemo connector to BNC Male		
Compatibility:	K9 camera system is compatible with all TSE Inc 900MHz video receivers.		
Weight:	2.07 lbs. with Batteries installed		
	1.80 lbs. with No Batteries installed		
Size:	2"H x 2.625"W x 9.75"D		

RECEIVER/MONITOR		
Frequency Range:	886Mhz-923Mhz (6 Channels, User-Selectable)	
Power Source:	Internal Rechargeable Lithium Polymer Batteries	
Charge Time:	4.5 hrs. Typical	
Operating Time:	2.5 hrs. Typical	
Operating Temp:	-20 to 60° C / -4 to 140° F	
Environmental:	Weather Resistant	
Antenna:	Removable 6-inch Omni Whip or Patch	
Video Output:	NTSC	
Operating Controls:	6 Channel Select, On-Off & Brightness	
Screen Size:	3.5 inch	
Interface Ports:	12 VDC Input, Video Output, Antenna	
Weight:	15.8 oz.	
Size:	6.17"W x 2.95"H x 1.31"D	



INCLUDED KIT COMPONENTS:			
Item	Part Number	NSN	
Waterproof K9 Camera/Transmitter	TSE-K9-XMTR-WP-3.5-V2	N/A	
Video Output Cable	TSE-K9-LEMO-BNC	N/A	
Receiver-Monitor	TSE-K9-RCVR	N/A	
Antenna Omni	TSE-ANT-OMNI	5985-01-599-3201	
Antenna Patch	TSE-ANT-PAT	N/A	
Power Supply, AC/DC 12 VDC w/2Pin	TSE-AC-DC-12W	6150-01-593-2993	
Case Set, Transport and Storage	TSE-K9-CASE	N/A	
K9 Camera Pouch	TSE-K9-POUCH-WP	N/A	
5590 to 2-Pin Cable	TSE-5590-2PIN	N/A	
Chest Mount for K9 Receiver	TBD	N/A	

Tactical Support Equipment Inc. 4039 Barefoot Road Fayetteville, NC 28306 www.tserecon.com

For More Information
Contact sales@tserecon.com





Phone: 800.889.4030 Phone: 910.425.3360 Fax: 910.425.3361